

2584 - SMOOTH BARK

Product Description:

2584 Smooth Bark displays the even and smooth bark of trees. The depressions are up to 5,6 mm deep, which creates an interesting play of light and shadow.

Composition:

2584 Smooth Bark is an embossed panel with special developed veneer and melamine resins with a plywood core.

Fields of application:

Only for interior: Interior fittings. Furniture manufacture. Shop and fair construction. Doors.

Technical Data:

First given measurement specifies the direction of embossment:

Invoiced size (mm): 2450 x 635 / 2450 x 1050
Delivered size (mm): 2450 x 635 / 2450 x 1050

Repeating pattern: No repeating pattern


Available thicknesses: 21 mm
Corebord: Plywood
Surface: raw, unlacquered

Density: ca. 840 kg/m³
Weight: ca. 18 kg/m²


Embossment: one-side
Deepness of structure: max. 5,6 mm

Tolerances:


Straightness: 3,0 mm per Meter
Size accuracy: +/- 1,0 mm per Meter
Thickness allowance: +/- 0,3 mm
Exactitude of profile: +/- 1,5 mm




Oak rustic
Real wood veneer



Oak smoked
Real wood veneer



Black Ash optic lacquered
Fineline veneer



Black clear matt lacquered
Fineline veneer

Explanatory notes:

The given details in this data sheet are our field-tested experience. They could not consider any parameter, use case or application and they are therefore without commitment. These data does not represent guarantee of condition in the legal sense or a assurance of the characteristics. No legal claims could be derived by using the information given in these data sheets or by our free of charge technical consultants. Images are for illustration purposes only. Wood is a natural product, deviations in color and texture can occur. Please visit our website for an impression of the color range, which can be expected.

Last update: 12.08.2022