

## 2668 - REED

### Product Description:

2668 Reed is a straight, round bar-shaped looking structure. The embossing has a width of 10 mm. The depth of the structure is 1,7 mm

### Composition:

2668 Reed is an embossed panel with special developed veneer and melamine resins with a particle board core.

### Fields of application:

Only for interior: Wall cladding, Interior fitout, shop and fair construction, doors.

### Technical Data:

First given measurement specifies the direction of embossment:

Invoiced size (mm): 3135 x 1270  
Delivered size (mm): 3145 x 1280

Repeating pattern: No repeating pattern

Available thicknesses: 18,5 mm  
Coreboard: Particle Board  
Surface: raw, unlacquered

Density: ca. 825 kg/m<sup>3</sup>  
Weight: ca. 16.5 kg/m<sup>2</sup>


Embossment: both sides  
Deepness of structure: 1,7 mm

### Tolerances:


Straightness: 3,0 mm per Meter  
Size accuracy: +/- 1,0 mm per Meter  
Thickness allowance: +/- 0,5 mm  
Exactitude of profile: +/- 1,5 mm



**Knob oak**  
Real wood veneer



**Heartwood walnut**  
Real wood veneer



**Lacquerable foil**

### Explanatory notes:

The given details in this data sheet are our field-tested experience. They could not consider any parameter, use case or application and they are therefore without commitment. These data does not represent guarantee of condition in the legal sense or a assurance of the characteristics. No legal claims could be derived by using the information given in these data sheets or by our free of charge technical consultants. Images are for illustration purposes only. Wood is a natural product, deviations in color and texture can occur. Please visit our website for an impression of the color range, which can be expected.

Last update: 07.02.2024