

2674 - RIPPLE

Product Description:

2674 Ripple represents traditionally hand-carved wood with a subtle waved texture.

The maximum depth of the embossment is 2 mm.

Composition:

2674 Ripple is an embossed panel with special developed veneer and melamine resins with a plywood core.

Fields of application:

Only for interior: Wall cladding, Interior fitout, shop and fair construction, doors.

Technical Data:

First given measurement specifies the direction of embossment:

Invoiced size (mm): 2450 x 1050

Delivered size (mm): 2450 x 1050

Repeating pattern: No repeating pattern

Available thicknesses: 18,5 mm

Coreboard: Plywood

Surface: raw, unlacquered

Density: ca. 845 kg/m³

Weight: ca. 18,5 kg/m²

Embossment: one side

Deepness of structure: max. 2,0 mm

Tolerances:

Straightness: 3,0 mm per Meter

Size accuracy: +/- 1,0 mm per Meter

Thickness allowance: +/- 0,5 mm

Exactitude of profile: +/- 1,5 mm



Knob oak
Real wood veneer



Black
Fineline veneer

Explanatory notes:

The given details in this data sheet are our field-tested experience. They could not consider any parameter, use case or application and they are therefore without commitment. These data does not represent guarantee of condition in the legal sense or a assurance of the characteristics. No legal claims could be derived by using the information given in these data sheets or by our free of charge technical consultants. Images are for illustration purposes only. Wood is a natural product, deviations in color and texture can occur. Please visit our website for an impression of the color range, which can be expected.

Last update: 20.09.2022