TECHNICAL DATA SHEET

HOLZ IN FORM

2720 - SHIFT

Product Description:
2720 Shift offers a modern interpretation of traditional wooden shingles. The staggered arrangement of the individual elements creates a lively, three-dimensional surface with a fascinating interplay of light and shadow.

Composition:
2720 Shift is an embossed panel with special developed veneer and melamine resins with a particle board core.

Fields of application:
Only for interior: Wall cladding, Interior fitout, shop and fair construction, doors.

Technical Data:
First given measurement specifies the direction of embossment:

Invoiced size (mm):	2450 x 1050
Delivered size (mm):	2450 x 1050
Repeating pattern:	No repeating pattern
Available thicknesses:	21 mm
Coreboard:	Plywood
Surface:	raw, unlacquered
Density:	ca. 900 kg/m3
Weight:	ca. 19 kg/m2
Embossment:	one side
Deepness of structure:	max. 6 mm

Tolerances:

Straightness:	3,0 mm per Meter
Size accuracy:	+/- 1,0 mm per Meter
Thickness allowance:	+/- 0,5 mm
Exactitude of profile:	+/- 1,5 mm



Knob oak
Real wood veneer



Old Oak
Real wood veneer



Larch smoked
Real wood veneer

Explanatory notes:
The given details in this data sheet are our field-tested experience. They could not consider any parameter, use case or application and they are therefore without commitment. These data does not represent guarantee of condition in the legal sense or a assurance of the characteristics. No legal claims could be derived by using the information given in these data sheets or by our free of charge technical consultants. Images are for illustration purposes only. Wood is a natural product, deviations in color and texture can occur. Please visit our website for an impression of the color range, which can be expected.

Last update: 29.10.2026